

## Description

This tape consists of a polyester film carrier coated on one side with a silicone rubber adhesive. Its adhesive has a high shear strength and temperature resistance. It is resistant towards aging and plasticisers.

## Carrier

Polyester film, 23 micron

## Liner

Hard PVC film, white, creped

## Adhesive

Silicone rubber

## Area of use

This rip-resistant tape adheres well to adhesive-repellent materials and is therefore suitable for use with silicone coated papers and silicone coated films.

## Technical data

<b>Thickness*</b> (adhesive + carrier)	60 micron	
<b>Temperature resistance***</b>	up to +180°C	
<b>LoopTack*</b> (FINAT TM 9)	10 N/25mm	
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel)	9 N/25mm	after 1 min
	10 N/25mm	after 20 min
	12 N/25mm	after 24 h
<b>Shear strength*</b> (FINAT TM 8, on stainless steel)	> 72 h	at 23°C
	> 1 h	at 70°C
<b>Temperature resistance*</b> (S.A.F.T.)	120°C	
<b>Shelf life**</b>	6 months	
<b>Application temperature</b>	> +15°C	

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.