

## Description

This double-sided tape consists of a paper tissue carrier, layered on both sides with a rubber adhesive. This adhesive has excellent bonding characteristics. It is lined with a double-sided silicone paper.

## Carrier

Paper tissue, 12,7 g/m<sup>2</sup>

## Liner

Both sides siliconised paper, 80 g/m<sup>2</sup>, brown

## Adhesive

Rubber

## Area of use

This tape is suitable as an adhesive medium for a variety of materials. Limited consistency in the presence of chemicals inclined to migrate (plasticisers).

## Technical data

<b>Thickness*</b> (adhesive and carrier)	90 micron	
<b>Temperature resistance***</b>	-40°C to +70°C	
<b>LoopTack*</b> (FINAT TM 9)	12 N/25mm	
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	13 N/25mm	after 1 min
	14 N/25mm	after 20 min
	15 N/25mm	after 24 h
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	>72 h	at 23°C
	3 min	at 70°C
<b>Temperature resistance*</b> (S.A.F.T.)	75°C	
<b>Shelf life**</b>	1 year	
<b>Application temperature</b>	> +15°C	

\* average      \*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.